

CHEETAH Two Components Hot Airless Spray Painting Equipment

The range is designed for tough working conditions and is suitable for two component high viscosity, solventless, low solvent coating, semisolid coating, marine coating, etc.

FEATURES

- Pneumatically sensed Air Motor
- High Flow Rate
- Stainless Steel rust proof Hydraulic Body
- Sophisticated automatic flow valve for remote control
- Easy Maintenance Ice Free Air Motor
- Easy to handle mounted on robust trolley
- Fixed I Variable mixing ratio
- Modular design to achieve various mixing ratios

OPTIONAL

- PLC based monitoring system for mixing ratio, digital display and auto flush.
- Electrical direct or oil water jacketed heating.
- High viscosity transfer pump with ram I drum press.

TECHNICAL SPECIFICATIONS

Type	2k-350/79 X 79 X 150	2k-350/110 X 110 X 110	2k-350/110 X 110 X 79	2k-350/110 X 110 X 58	2k-350/275
Mixing Ratio	1:1	2 :1	3 :1	4 :1	0:1 to 10 :1
Transfer Ratio	70:1	65:1	70:1	75:1	75:1
Output per Cycle	300 cc	340 cc	300 cc	280 cc	275 cc
Air Motor Piston Ø	350 mm	350 mm	350 mm	350 mm	350 mm
Stroke Length	120 mm	120 mm	120 mm	120 mm	120 mm
Recommended Spray Volume per minute.	7.5/tr.	8.5Itr.	7.5Itr.	7.0Itr.	7.5Itr.
Air Inlet Pressure Max.	6 bar	6 bar	6 bar	6 bar	7 bar
Output Pressure Max.	420 bar	390 bar	420 bar	450 bar	525 bar
Air Consumption N Itr I min Max.	6800	6800	6800	6800	6800