

PORTABLE ABRASIVE BLASTERS - SPECIFICATIONS

	P7-150	P7-301R	P7-501R	P7-901R	P7-1001R
Abrasive Capacity					
Metallic (Kg.)	150	300	500	900	1000
Sand (Kg.)	65	130	230	400	460
Volume (Litres)	42	85	142	255	284
Overall dimensions approx					
Height mm	1110	1290	1370	1610	1610
Diameter mm	360	460	615	615	760
Weight Kg.	95	140	180	220	245
Blast Nozzle Tungsten Carbide lined					
Orifice mm [*Standard size supplied unless ordered otherwise]	*5 6	*6 5	*8 6, 10	*10 8, 12	*10 8, 12
Blast Hose ID (mm)	19	19	25	32	32
Blast Hose Length (metre)	5	5	7.5	10	10
Recommended Air Hose ID (mm)	19	19	25	32	32
Approx Cleaning rate (sq. Mtr./hour)					
For guidance only	3 to 4	5 to 9	11 to 15	15 to 19	15 to 19
Compressed Air Requirement at 5.63 Kg./sq. Cm (80psi)					
Cubicmetre/minute (Cfm.)	1.27(45)	2.41(85)	3.85(135)	7.08(250)	7.08(250)
Recommended Abrasive size range BS Mesh	30 to 80	25 to 80	16 to 80	12 to 80	12 to 80