

## TIGER Medium Duty Airless Equipment

The range is suitable for liquids of medium viscosities, primers, finish paints and paints of medium viscosity & particle size.

### FEATURES:

- Pneumatically sensed high performance Air Motor(No overcenter spring loaded mechanical changeover)
- High Flow Rate
- Stainless Steel rust proof Hydraulic Body
- Easy Maintenance
- Ice Free Air Motors
- **Light and Easy to handle**

### TECHNICAL SPECIFICATIONS

Type	30.70	40.110	12.150	28.20	30.150	28.40	60.70	16.70	12.150	14.20	14.40
Transfer Ratio*	30:1	40:1	12:1	28:1	30:1	28:1	60:1	16:1	12:1	14:1	14:1
Output per Cycle	70	110	150	20	150	40	70	70	150	20	40
Air Motor Piston Ø	110	160	110	80	160	80	160	80	110	60	60
Stroke Length	120	120	120	70	120	120	120	120	120	70	120
Recommended Spray Volume per minute	3.5	5.5	7.5	2	6	1.5	3.5	3.5	7.5	1.2	1.2
Air Inlet Pressure Max.	8	8	6	6	8	8	6	8	6	6	6
Output Pressure Max.	240	320	72	168	240	224	360	128	720	84	84

Air Consumption N ltr/min Max.	900	1900	900	450	1900	400	1400	450	900	250	250
--------------------------------------	-----	------	-----	-----	------	-----	------	-----	-----	-----	-----